

**BELT DRESSING SPRAY
ISOL BD 601**

ISOL BD 601 prevents belt slippage, improves the life of the belt and optimizes the output of the belt drive. Its tacky polymeric formulation provides the necessary friction to prevent slippage and yet acts as a lubricant between the pulley and the belt.

FEATURES

- Optimizes belt tension and reduces the need for tightening.
- Conditions V-belts and fan belts to prolong belt life.
- Prevents premature wearing.
- Promotes better grip and traction.
- Reduces squeaks and chattering.
- Reduces strain on bushings and bearings.
- Provides lubrication to the contacting surface of the belt and pulley.

TYPICAL SPECIFICATIONS

Color	Water white, transparent.
Actives	Polymer material.
Propellant	Hydrocarbon Gas

METHOD OF USE

Attach extension tube to the nozzle and shake the can well before use. Spray liberally on the exposed groove of the pulley while the pulley is idling. Wait for 10 minutes to allow the sprayed liquid to become semi dry and tacky and then run the equipment.

APPLICATIONS

All kinds of belt drive in machines and automobiles etc.

CAUTION

This is a pressurized aerosol can. Do not punctured, heat or incinerate. Store away from sunlight and other heat sources. Do not spray on flame or heat sources. Do not store above 50 °C. Use in a well-ventilated area and avoid excessive inhalation, eye or skin contact.

SHELF LIFE

The Cans should normally be used with in twelve months from date of manufacture.

PACKING

12can of 300 gm. each are packed in one corrugated box.

The information herein is believed to be reliable, but it is the user's responsibility to determine suitability of use, since we cannot know conditions of use. We make no warranties and assume no liability concerning use of the information. Nothing herein should be taken as inducement to infringe any patent.